

SPECIFICATIONS

STYLE NAME: OTERRA™	APPROX. WEIGHT PER CARTON: 30.04 LBS.
ABRASION CLASS: AC4 CLASS 32	CARTON SIZE: 7.91"W X 51.18" L X 2.60"H
LOCKING SYSTEM: ANGLE TAP	CARTONS PER PALLET: 68
FINISH: EIR (EMBOSS IN REGISTER)	SQUARE FEET PER PALLET: 903.04 SQ. FT.
BEVEL: 4 SIDED PAINTED MICRO BEVEL W/ WATER REPELLANT COATING	APPROX. WEIGHT PER PALLET: 2,080.72 LBS.
NOMINAL PRODUCT THICKNESS: 14MM TOTAL (12MM + 2MM PAD)	PALLETS PER 40 FT. CONTAINER: 20
NOMINAL PLANK SIZE: 8.03" W X 47.64"L x 0.55" H	SQUARE FEET PER 40 FT. CONTAINER: 18,060.8 SQ. FT.
UNIQUE PLANKS PER SKU: 7	APPROX. WEIGHT PER 40 FT. CONTAINER: 41,614.4 LBS.
PLANKS PER CARTON: 5	COUNTRY OF ORIGIN: MANUFACTURED IN USA WITH GLOBAL COMPONENTS
SQUARE FEET PER CARTON: 13.28 SQ. FT.	

PERFORMANCE

CARB PHASE II: TSCA Title VI Compliant	NALFA 3.9 CHAIR RESISTANCE: CLASS 4
ASTM E648 CRITICAL RADIANT FLUX: CLASS 2	NALFA 3.1 STATIC LOAD: CLASS 3
ASTM E662 SMOKE DENSITY: UNDER 450	NALFA 3.5 LARGE BALL IMPACT RESISTANCE: CLASS 3
NALFA 3.3 XENON LIGHT RESISTANCE: CLASS 3	NALFA 3.6 SMALL BALL DART IMPACT: CLASS 2
NALFA 3.4 CLEANABILITY – STAIN RESISTANCE: CLASS 3	AATCC 134 (STEP) ELECTROSTATIC: 1.9 K.V.
NALFA 3.7 WEAR RESISTANCE: CLASS 3	NALFA 3.2 THICKNESS SWELL: CLASS 3
NALFA 3.10 SURFACE BOND: CLASS 3	NALFA 3.2 THICKNESS SWELL: CLASS 3
NALFA 3.8 DIMENSIONAL TOLERANCE: CLASS 4	ASTM E90: STC Rating 60
ASTM E492: IIC 60	

INSTALLATION

END USE: RESIDENTIAL, COMMERCIAL	RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION METHOD: FLOAT	INSTALLATION SUNDRIES AS REQUIRED: 6 MM POLYETHYLENE SHEETING
SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST	

DESIGN

PART NUMBER

EAN / UPC NUMBER

DESIGN	PART NUMBER	EAN / UPC NUMBER
STARGAZER OAK 994E	62002430	190670032576
RIVERSTONE OAK 904D	62002431	190670032583
HIGHLAND OAK 626D	62002432	190670032590
PRAIRIE OAK 624M	62002433	190670032606
RIVIERA OAK 169M	62002434	190670032613
CHILEAN OAK 946M	62002435	190670032620
URBAN OAK 919M	62002436	190670032637
NORDIC ASH 296L	62002437	190670032644
ICELANDIC BEECH 021L	62002438	190670032651
DOVER OAK 009S	62002439	190670032668

WARRANTIES

LIMITED LIFETIME RESIDENTIAL WEAR, FADE, STAIN, JOINT & TOPICAL 72 HR MOISTURE WARRANTY

15 YEAR COMMERCIAL WEAR, FADE, STAIN, JOINT & TOPICAL MOISTURE WARRANTY

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER SPECIALLY FORMULATED FOR USE WITH LAMINATE AND A MICROFIBER MOP.