



HF9200 Luxury Vinyl Plank & Tile Flooring Adhesive

PRODUCT CHARACTERISTICS

HF9200 Adhesive is a versatile spray adhesive naturally suited for adhering approved Luxury Vinyl Tile, Luxury Vinyl Plank and Carpet Tile in commercial and residential applications.

It uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. Its instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

It is a non-toxic, 0.0 g/mL VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.0 g/mL VOC content
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

COVERAGE

For approved LVT, LVP and Carpet Tile in an upside down aerosol can.

150-185 sq ft per can

SUITABLE SUBSTRATES

HF9200 Adhesive bonds approved LVT, LVP, and Carpet Tile to the following properly prepared, smooth, flat, dust-free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

TECHNICAL CHARACTERISTICS

- Provides immediate shear strength after installation allowing instant access to finished floor
- Solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B
- Uses non-ozone depleting HFC propellant
- Withstands 8 lbs. of vapor emissions 98% RH and 11 pH

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



Information

Chemical Type	Water-based acrylic blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash Point	Will not burn
NFPA 704 Flammability Rating	0 (Non-Flammable)
Shelf Life	3 years, if unopened
Open Time	4 hours
Dry Time	Once adhesive is dry to touch (10-20 minutes)
VOC Content	0.0 g/mL calculated per EPA Test Method 8260B
Foot Traffic Allowance	Immediately
Heavy Machinery Allowance	Immediately
Resistance to Moisture	Excellent: 8 lbs/1,000 sq ft or 98% RH/11pH
Underfloor Heating Systems	Yes
Storage	Do not subject to freezing temperatures



HAPPYFEETINTERNATIONAL.COM

529 Rollins Industrial Blvd
Ringgold, GA 30736
706.937.2500